


Product data sheet

STORMBELL 80 SU RE 1500 WW WFL BK/BK+ ACC. BELL STORMBELL 80 Ø227X89 BK
ST18SELOWF930NBB+S8BE227B
LAMP



Downlight to suspend model STORMBELL 80 SU RE 1500 WW WFL BK/BK LAMP brand. Body made of injected aluminum with white/black/Materiality finish, and with black/opal polycarbonate ring, for decorative lighting effect and possibility of accessory color filter, depending on his model. COB LED 3000K color temperature and CRI90. Aluminium reflector WIDE FLOOD. Luminaire with ceiling rose and electronic equipment included. Insulation class I. LED life time: 50000 L90 B10. Compatible with 4 different models of bells (accessories) that complete the luminaire. + Accessory for suspended luminaries modell ACC. BELL STORMBELL 80 Ø227x89 BK LAMP brand. Body made of aluminum with white/black/Materiality finish.

Light output 1



1 x LED			
Nominal lamp power	14.5 W	LOR	99%
Lamp flux	1149 lm	Total flux	1141 lm
Luminous efficacy	79 lm/W	Total power	14.5 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Height: 3.50 in
Diameter: 8.94 in

Adjustability

Fixed

Electric

System power: 14.5 W
Appliance Class: I

Protection

IP: 20