

Product data sheet

NORA III
9.773.3046.05
LEIPZIGER LEUCHTEN



For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier , painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of supply includes special steel post bracket, painted -Order post dia. 60 mm/ dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	76%
Lamp flux	2000 lm	ULOR	2%
Luminous efficacy	26 lm/W	Total flux	1524 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	76%
Lamp flux	4000 lm	ULOR	2%
Luminous efficacy	34 lm/W	Total flux	3048 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted, Ceiling mounted

Shape and measurements

Height: 11.81 in
Diameter: 21.26 in

Design

Material impression: Matt

Electric

System power: 59-89 W
Ballast: ECG
Controller: DALI

Protection

IP: 55
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F