

# Product data sheet


RWY 2000 L40 ER MP  
RUNWAY (CONTINUOUS RUN)  
DEXTRA



IP  
20

Runway Continuous Surface/Suspended - 2000mm Continuous run surface/suspended end of run linear luminaire, extruded aluminium trunking with painted finish and microprism diffuser. Options: E3 - Emergency control gear (364 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence RWY 1500 MP - Runway 1500mm Microprism diffuser RWY 1500 EA MP - Runway 1500mm EA Microprism diffuser RWY 1500 R24H MP - Runway 1500mm R24H Microprism diffuser RWY 1500 TW - Runway 1500mm though wire trunking WH - White trunking BL - Black trunking RWY SUSP 3M - Runway 3M single point suspension kit RWY SMK - Runway Surface Mount kit (single point) RWY EC 95 GREY - Runway End Cap (pair) RWY INSTALL KIT - Runway Installation Kit (1 Kit per installation)

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24.5 W	CRI	80
Total flux	2760 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	4%
		Total power	24.5 W

## Mounting mode

Ceiling mounted, Pendant

## Shape and measurements

Length: 77.48 in  
Width: 3.54 in  
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 24.5 W

## Protection

IP: 20