


Product data sheet

LOTIS 86 IP55 FOR LED 4000K MEDIUM GE ALU STRUC
13090028+14061005
MODULAR




Modular's holy lighting grail Lotis is the recessed spotlight which started it all. The hallmark of this luminaire, is the deeply recessed cone which holds the light source and has a fine edge. The complete Lotis range comes in an upgraded Lotis for LED version, using our M-LED 50 module. This allows you to choose from a large range of lighting colours (2700-4000K) and three different beam angles (spot, medium or flood).

Light output 1



1 x LED			
Nominal lamp power	6.2 W	LOR	79%
Lamp flux	590 lm	Total flux	464 lm
Luminous efficacy	75 lm/W	Total power	6.2 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	9.2 W	LOR	79%
Lamp flux	792 lm	Total flux	622 lm
Luminous efficacy	68 lm/W	Total power	9.2 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.39 in
Width: 3.39 in
Height: 1.89 in
Weight: 0.16 kg

Adjustability

Fixed

Electric

System power: 6.2-9.2 W

Protection

IP: 55