


Product data sheet

GUIDELED SL 13022.1 CG-S
40071354483
EATON EMERGENCY LIGHTING



• Safety luminaire with LED technology for surface mounting • Slender, discrete design with low height of 32mm • Special LED optics ensure especially efficient escape route illumination or uniform anti-panic illumination • High Spacing by exact light direction and highly-efficient HighPowerLEDs • Up to 27 m from luminaire to luminaire with optics for escape route illumination • Up to 12 m from luminaire to luminaire with optics for antipanic illumination • Minimum service requirement due to high service life of the LEDs (50,000 hours)

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6000 K
Nominal lamp power	3.9 W	CRI	65
Total flux	250 lm	LOR	100%
Luminous efficacy	64 lm/W	Total power	3.9 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.88 in
Width: 4.88 in
Height: 1.18 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 3.9 W
Suitable for feed-through wiring
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 41
IK: 03