Product data sheet

MINI MULTIPLE TRIMLESS FOR SMART LOTIS LED 3000K FLOOD GE BLACK 12535102+12555102

MODULAR









Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your chouce. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with Smart by adding the Smart frontrings to your recessed spot.

Light output 1



| 6.2 W |
|---------|
| 550 lm |
| 75 lm/W |
| 3000 K |
| 90 |
| |

| LOR | 85% |
|-------------|--------|
| Total flux | 467 lm |
| Total power | 6.2 W |
| | |



| 1 x LED | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 9.2 W | LOR | 85% |
| Lamp flux | 739 lm | Total flux | 627 lm |
| Luminous efficacy | 68 lm/W | Total power | 9.2 W |
| CCT | 3000 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Length: 4.72 in Width: 4.72 in Height: 4.72 in Weight: 0.69 kg

Adjustability

Free

Electric

System power: 6.2-9.2 W Appliance Class: III

Protection

IP: 20 IK: 01