

# Product data sheet


RV RIDGEVIEW LED  
LDRV-SL3-E01-E-8030-HSS  
COOPER LIGHTING



IP  
47

One-piece, die-cast aluminum housing can be pole or wall-mounted, Optical design creates consistent distribution and scalability, Choice of 12 high-efficiency, patented AccuLED Optics™, Standard in 4000K (+/- 275K) CCT and nominal 70 CRI, Suitable for operation in -40°C to 40°C ambient environments, 120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation, Proprietary circuit module withstands 10kV of transient line surge, Optional battery pack and bi-level switching, Five-year warranty

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 24.7 W  | CRI         | 75     |
| Total flux         | 1419 lm | LOR         | 100%   |
| Luminous efficacy  | 57 lm/W | Total power | 24.7 W |

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 2.04 in  
Width: 12.00 in  
Height: 1.20 in

## Adjustability

Fixed

## Electric

System power: 24.7 W

## Protection

IP: 47