

# Product data sheet


VENICE-E-F1X154-11-NE + G-R1X115/30ND-SRM-500M840  
0528270AF + 0526116 + 0208933  
RIDI



IP  
20

Recessed light channel Design: VENICE-E-R is a narrow, rectangular LED light channel comprising a recessed carrier profile in natural anodised (-NE) extruded aluminium with longitudinal rim to cover the sawn edge, gear tray in white coated steel and optical control. A matt parabolic louvre (SM) is available for optical control. For R-TUBE lamps (order separately). The luminaires come in a 1, 2 or 3-length version. Gear tray in profiled galvanised white coated steel. End caps must be ordered separately (see accessories). Gear trays can be mounted at any optional position in the mounting rail. Quick-release plastic coated catches for fastening in the carrier profile. Units with 3-circuit lighting tracks are designed to accommodate spotlights. For blank areas within the light channel, dummy luminaires are available. These are covered by natural anodised sectional extruded aluminium. Electronic converter for LED, 230 Volt, 0/50-60 Hz, wired to electrical adapter with phase selection by means of sliding contact. Suitable for direct voltage operation and use in central battery systems. Mounting: Carrier profile with key holes for permanent fixture spacing or mounting fixing kit and with T-groove to accommodate lengthways sliding fixing elements. Narrow visible rim to cover the sawn ceiling aperture. L, T and X shaped connectors are available for the creation of VENICE lighting constructs, see accessories. For almost rimless mounting, the surface-mounting light channel VENICE-A can also be mounted and concreted in using a suitable fixing kit. VENICE-E-R ... SM For creating a recessed light channel with parabolic mirror louvres SM, made of high-reflectance matt anodised super-purity aluminium with silver coating. For lamp R-TUBE, recommended cover: matt.

## Light output 1



1 x LED			
Nominal lamp power	34 W	LOR	75%
Lamp flux	4780 lm	Total flux	3596 lm
Luminous efficacy	106 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 47.56 in  
Width: 3.15 in  
Height: 3.86 in

## Adjustability

Fixed

## Electric

System power: 34 W

## Protection

IP: 20