


Product data sheet

FLAT POLYMERO
672059.002.5.04
RZB




IP
40

IK
03

Item Number: 672059.002.5.04 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, single battery system, automatic self-test with bus connection for feedback to the RZB Multidigit, RZB MWEBplus and S63 monitoring systems. Additional status display on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, , H 120mm Lamp: LED + LED 1.5 W Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: MultiDigit Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 22W Beam Angle: 111° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 8,1 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	0.1 W	CRI	80
Total flux	100 lm	LOR	100%
Luminous efficacy	1000 lm/W	Total power	0.1 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.72 in

Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 0.1 W

Protection

IP: 40

IK: 03