Product data sheet


KOCCA 3.2 T [3000K 36W 230VAC]
KA32115TE
L&L LUCE&LIGHT



IP 65 IK 05


Wall mounted for outdoor applications, double beam; surface mounted (wall); body in die-cast aluminium alloy EN AB 47100, screen in tempered glass; finishes: anthracite, white, cor-ten, grey; optics version: 10 (5+5) power LEDs, 18 (9+9) power LEDs, diffuse version: power LED matrix; optics version: 21W (10 power LEDs), 36W (18 power LEDs); diffuse version: 15W - 230Vac; built in power supply unit; connection box with 0,50 m cable H05RN-F 2x0,75 Ø6,3 mm; total delivered lumens: optics version: 631 lm (3000K, 10 power LEDs), 1137 lm (3000K, 18 power LEDs) per emission, diffuse version: 441 lm (3000K) per emission; optics: 7°, 10°, 30°, diffuse; LED colour: white - 2700K, 3000K, 4000K, 5000K; ingress protection: IP65; impact resistance: IK05; operating temperature: -10°C +45°C; screen temperature: max 40°C (Ta 25°C); Glow Wire Test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: I; weight 4,00 kg; dimensions 150x150x170 mm; accessories: spacer WD0400F / WD0400E / WD0400R / WD0400H

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	1057 lm	LOR	100%
Luminous efficacy	59 lm/W	Total power	18 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	1057 lm	LOR	100%
Luminous efficacy	59 lm/W	Total power	18 W

Mounting mode

Wall mounted

Shape and measurements

Length: 5.90 in
Width: 6.61 in
Height: 5.91 in

Electric

System power: 36 W
Appliance Class: I

Protection

IP: 65
IK: 05

Adjustability

Fixed