
Product data sheet

IP 12L70-740 WR BPS CL2 T76F ANT W6
96275976
THORN LIGHTING



A state of the art LED road lighting lantern with 12 LEDs driven at 700mA with Wide Road optic. Electronic, fixed output control gear. Class II electrical, IP66, IK09. Housing: die-cast aluminium, powder coated textured anthracite (close to RAL7024). Spigot: die-cast aluminium, powder coated anthracite (close to RAL7024). Enclosure: 5mm thick glass. Fixings: stainless steel. Supplied with Ø76mm spigot adaptor pre-fitted for post-top, 5° tilt. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Pre-wired with 6m cable. Complete with 4000K LED. Surge protection: 10kV single pulse common mode and 8kV multipulse common mode and 6kV multipulse differential mode. If permanent DALI system is connected, 6kV multipulse common and differential mode. Dimensions: 571 x 224 x 114 mm Total power: 28 W Luminaire luminous flux: 3460 lm Luminaire efficacy: 124 lm/W Weight: 6.24 kg Scx: 0.05 m²

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	70
Total flux	3460 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	28 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 22.48 in
Width: 8.82 in
Height: 4.49 in
Weight: 6.2 kg

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 28 W
Voltage: 230 V AC
Appliance Class: II

Protection

IP: 66
IK: 09
Designation labels: CE