Product data sheet

SILVERBACK SUSPENDED Ø295 LED 3000K 9.8W 5741091674

LOUIS POULSEN








Silverback Ceiling/Wall Design: KiBiSi Light concept: The fixture emits diffused light. The opal curved diffuser provides a soft and comfortable spatial lighting, and the metallised rear half of the product produces a decorative halo-like illumination on the ceiling or wall surface. The metallised surface also creates a mirror effect, reflecting the texture, colour or material of the installation surface. Finish: White opal and alumetallised. Material: Rear housing: Die-stamped steel sheet, powder coated, white. Diffuser: Opalescent PMMA and semi-metallised PC. Mounting: Terminal strip: 1x5x2.5mm2. Cable access: 2 rear, Ø19mm. Looping: Approved, max. 5x1.5mm2. Weight: Max. 3 kg Class: Ingress protection IP20. Electric shock protection I w. ground.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.8 W	CRI	90
Total flux	817 lm	LOR	100%
Luminous efficacy	83 lm/W	ULOR	7%
		Total power	9.8 W

Mounting mode

Pendant

Shape and measurements

Height: 4.09 in Diameter: 11.61 in

Adjustability

Fixed

Electric

System power: 9.8 W Appliance Class: I

Protection

IP: 20