Product data sheet


FREESTANDING LUMINAIRE NEO+ OFFICE SINGLE PART LUMINAIRE HE
2010.0474 - NEO+ T LED12200-830 BK IF2C EU
REGENT



IP 20

Freestanding luminaire Neo+ Office single part luminaire head, with LED, system power: 81 W, standby power 0.5 W, luminous flux of luminaire 12200 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 10; Lmax ≥ 65° ≤ 1500 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.36 A, direct-indirect light emission, 15%/85%, independently dimmable and switchable, with control element (2-channel) on the rod, one-piece housing in die-cast aluminium, black, RAL 9005, -DM (deep matt), thermo painted, CLD+ optics (Controlled Luminance Diffuser) for perfect office-grade glare control, integral control gear, dimmable digital, with light/movement sensor, base plate, T-shaped, 3m power supply cable with IEC 7/7 european plug, protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1591875 total height = 2000 mm L = 720 mm, B = 337 mm,

Light output 1



1 x LED

Nominal lamp power	81 W	LOR	100%
Lamp flux	12200 lm	ULOR	85%
Luminous efficacy	151 lm/W	Total flux	12196 lm
CCT	3000 K	Total power	81 W
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 28.35 in
Width: 18.90 in
Height: 78.74 in
Weight: 13.664 kg

Adjustability

Free

Design

Color of housing: Black

Electric

System power: 81 W
Appliance Class: I

Protection

IP: 20