


Product data sheet

CIRCULAR OUTWARD Ø1200 SURFACE
CF4B-00W9AZOU14
LEDSC4



LedsC4 Circular Outward ø1200 Surface CF4B-00W9AZOU14V1 Pendant for indoor use. For sideways lighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 6 Product width or diameter (mm): 1177 Product height (mm): 3000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 67.4W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 8.7. Photobiological risk: RG1. Real flux (lm): 5663. Real lm/W: 79. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 72. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	72 W	LOR	100%
Lamp flux	5663 lm	ULOR	49%
Luminous efficacy	79 lm/W	Total flux	5664 lm
CCT	3000 K	Total power	72 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 47.24 in
Width: 47.24 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 72 W
Appliance Class: I

Protection

IP: 20