


Product data sheet

COLUMBUS 1 BOLLARDS
CO-10117-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Anodised, high-purity aluminium reflector - Clear, impact-resistant, UV-stabilised polycarbonate diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	40.8 W	CRI	80
Total flux	995 lm	LOR	100%
Luminous efficacy	24 lm/W	ULOR	21%
		Total power	40.8 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 28.50 in
Diameter: 8.54 in
Weight: 8.4 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 40.8 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 55
IK: 08
Surface temperature: 40°C