

Product data sheet


AMEX L20 OB
AMENITY EXTERIOR LED
DEXTRA



IP
65

Amenity Exterior - IP65, IK10 Surface mounted Exterior Luminaire, die cast aluminium body, finished in black powder coat paint, opal polycarbonate diffuser. Options: LE3 - Lithium Emergency (197 lumens) LS3 - Lithium Selftest LA3 - Lithium Autotest A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* S - Switch Dimming D - Digital Dimming (DSI) R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode* *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.5 W	CRI	80
Total flux	1145 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	4%
		Total power	13.5 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Height: 4.17 in

Diameter: 14.17 in

Adjustability

Fixed

Electric

System power: 13.5 W

Protection

IP: 65