Product data sheet


LOUI BEAMLINE
921566.0045
RZB



IP 20 IK 03


Series: LESS IS MORE BEAMLINE system Colour: silver, matt (approx. RAL 9006) Length: 2242 mm Width: 71 mm Height: 1.5 mm Recess height: 125 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 90 System power: 47 W Rated luminous flux: 4100 lm Beam angle Down: 44° Luminous efficiency: 87 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.75 W	CRI	90
Total flux	1025 lm	LOR	100%
Luminous efficacy	87 lm/W	ULOR	13%
		Total power	11.75 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.75 W	CRI	90
Total flux	1025 lm	LOR	100%
Luminous efficacy	87 lm/W	ULOR	13%
		Total power	11.75 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.75 W	CRI	90
Total flux	1025 lm	LOR	100%
Luminous efficacy	87 lm/W	ULOR	13%
		Total power	11.75 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.75 W	CRI	90
Total flux	1025 lm	LOR	100%
Luminous efficacy	87 lm/W	ULOR	13%
		Total power	11.75 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 88.27 in
Height: 0.08 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 47 W

Protection

IP: 20
IK: 03