

Product data sheet

CALIDO EVO
741701.004.1
RZB




IP
20

IK
04

Series: Calido EVO Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: die-cast aluminium, powder-coated. Transparent safety glass, "partially UV-absorbent. Faceted aluminium reflector, highly polished anodised finish. Rotation range: 356°;" swivel range: 180°. LED incorporated. Tool-free bayonet lock system. Control gear incorporated. With multi adaptor for 230 V 3-circuit tracks. LED included. Available Colours: silver, metallic Type of Installation: Track on ceiling Dimensions: L 186, B 100, H 162 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK04 (0,50 Joule) Luminaire flux LED: 2150lm System power: 31W Beam Angle: 30° Number of fittings B10A: 9 Number of fittings B16A: 15 Inrush current: 16A Unified Glare Ratio: 19,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	31 W	CRI	80
Total flux	2150 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	31 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.94 in

Width: 7.32 in

Height: 5.12 in

Adjustability

Rotatable, Tilttable

Electric

System power: 31 W

Protection

IP: 20

IK: 04