Product data sheet

TORSTEN III DA LED (OPTIC 098)
9.003.8207.17098-3
LEIPZIGER LEUCHTEN



IP 65

recom. pole height: 3.00m – 5.00m light standards: for medium lighting requirements lamp: inkl. 2 DA+ (2x4) LED modules colour temperature: 4.000K neutral white or 3.000K warm white surge protection: 10kV LED gear: incl. 4DIM driver, up to 100,000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire life time; AC/DC compatible for operation with central battery systems LED life expectancy: up to 100,000 hours, 50,000 hours/ L100/ B10 for minimum maintenance costs due to an excellent thermal management optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: deep wide beam; others on request luminaire head: canopy made of aluminium with a special white, reflective underside finish, base made of corrosion-resistant cast aluminium; powder coated colour: RAL or DB glazing: PMMA RESIST, clear, high-impact wiring: via a plug and socket connector outside the luminaire head; easy installation installation: for top entry ø 76mm accessory: column, cable , pole accessories, light shut for non-glare on the rear side (equipped with max. 4 per luminaire) - to be ordered separately application areas: for parkways, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, paths, cycle lanes, squares, car parks, shopping center, pedestrian zones

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	70
Total flux	1903 lm	LOR	68%
Luminous efficacy	127 lm/W	ULOR	34%
		Total power	15 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 21.65 in
Diameter: 7.87 in
Weight: 8.9 kg

Adjustability

Height adjustable

Design

Color of housing: Other colors

Electric

System power: 15 W

Protection

IP: 65