


Product data sheet

CALLISTO WHITE 200LM 2700K RA>80 TRAILING EDGE DIMMING
7021989120124
SG ARMATUREN



Good little LED luminaire for walls and ceiling. For both outdoor and indoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, powder coating and 10-year corrosion warranty, glass diffuser. 33 cm in total height, KL II means that it can be mounted without earthing, direct 230 V with loopable quick clips. Light distribution Direct Light technic LED (not exchangeable) 3W 2700K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK06 Energy and approvals CE Materials and finish Housing: Aluminium Colour: Matte white (RAL 9003) Optics: Glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 115, B16: 184, C10: 134, C16: 215

Light output 1



1 x LED

Nominal lamp power	3 W	LOR	100%
Lamp flux	200 lm	Total flux	200 lm
Luminous efficacy	67 lm/W	Total power	3 W
CCT	2700 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.33 in

Width: 4.33 in

Height: 1.06 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 3 W

Appliance Class: II

Protection

IP: 65

IK: 06