
Product data sheet


SYSTEM BATTEN LUMINAIRE PURELITE HE (HIGH EFFICIENCY) M1200
2009.2557 - PURLT INS1200 MID MAS HE LED-840 DALI
REGENT



IP 20


System batten luminaire Purelite HE (High Efficiency), m1200, intermediate module, Master, with LED, system power: 14 W, standby power 0.5 W, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission 1 integral control gear, DALI2, support profile and system components to be ordered separately System batten luminaire Purelite protection class I, ingress protection IP20, this product contains a light source of energy efficiency class A and EPREL registration number: 1564293 L = 1200 mm, B = 68 mm, H = 19 mm

Light output 1




1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	1860 lm	ULOR	13%
Luminous efficacy	89 lm/W	Total flux	1860 lm
CCT	4000 K	Total power	14 W
CRI	80		




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	1440 lm	Total flux	1440 lm
Luminous efficacy	39 lm/W	Total power	14 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	18.8 W	LOR	100%
Lamp flux	1800 lm	Total flux	1800 lm
Luminous efficacy	96 lm/W	Total power	14 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	18.8 W	LOR	100%
Lamp flux	1980 lm	ULOR	13%
Luminous efficacy	105 lm/W	Total flux	1980 lm
CCT	4000 K	Total power	14 W
CRI	80		



1 x LED

Nominal lamp power	17 W	LOR	100%
Lamp flux	1980 lm	Total flux	1981 lm
Luminous efficacy	116 lm/W	Total power	14 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 47.20 in
Width: 3.54 in
Height: 1.38 in
Weight: 0.899 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 14 W
Appliance Class: I

Protection

IP: 20