

Product data sheet

OFFICE LIGHTING
V1-R3-00069-300PD-4001650 GR170/F 2.0 610X202X50 MM IP40 16W 5000K OPAL DALI
VARTON




IP
40

IK
03

Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: YXЛ4 Height/depth, mm: 50 Length, mm: 610 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK03 Width, mm: 202 Power factor: 0,95
https://www.varton.ru/products/ofisnoe-osveshchenie/var-ton-dlya-grilyato-gr-seriya-2-0/gr170-f-2-0-610x202x50-mm-ip40/svetodiodnyy-svetilnik-var-ton-gr170-f-2-0-16-vt-5000-k-s-rasseivatelem-opal-610kh202kh50-mm-s-planka_2/

Light output 1



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1680 lm	Total flux	1680 lm
Luminous efficacy	105 lm/W	Total power	16 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 24.02 in
Width: 7.95 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 16 W

Protection

IP: 40
IK: 03