Product data sheet


HALYXX
671750.002.1.04
RZB



IP 40 IK 03

Series: HALYXX Luminaire for escape route identification. Installation housing sheet steel. Ceiling plate stainless steel high polish or powder-coated. Display panel: highly transparent panel, plastic, with legend on one side/both sides. Electronic ballast included. Self-contained system with automatic self-test and feedback to the RZB monitoring system MULTIDIGIT. Please indicate legend number when placing your order! Colour: white Length: 320 mm Width: 55 mm Height: 140 mm Cut-out length: 305 mm Cut-out width: 42 mm Recess height: 90 mm Weight: 1.66 kg Operating mode: maintained power mode Viewing Distance: 19 m Duration time: 3 h Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 3.2 W Rated luminous flux: 55 lm Luminous flux, emergency: 30 System power, emergency: - Control gear: Electronic transformer Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	0.01 W	CRI	80
Total flux	1 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	15%
		Total power	0.01 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.17 in
Width: 12.60 in
Height: 5.51 in

Adjustability

Fixed

Electric

System power: 0.01 W

Protection

IP: 40
IK: 03