


# Product data sheet

PLURIO OR 70W/BP HSE 240V CL1 ECL D76  
96253972  
THORN LIGHTING



Decorative, post-top lantern for 70W HSE lamp, using ZRMU6M equipped bi-powered magnetic gear. Class I electrical, IP66, IK08. Base in cast aluminium, powder coated silver-grey. Canopy in original shape, made from aluminium textured silver-grey (close to RAL9006). UV stabilised polycarbonate clear diffuser. Multi-facetted aluminium reflector.. Supplied complete, in one box. Lamps to be ordered separately. To be post top mounted on a spigot of Ø76mm, length 100mm. It is recommended that powdered ellipsoidal lamps are used with clear diffusers and clear tubular lamps are used with opal diffusers. Dimensions: Ø564 x 567 mm Total power: 85 W Weight: 9.07 kg Scx: 0.074m²

## Light output 1



### 1 x General service incandescent lamp

Nominal lamp power	70 W	LOR	69%
Lamp flux	5800 lm	Total flux	4020 lm
Luminous efficacy	47 lm/W	Total power	85 W
CCT	3000 K		
CRI	20		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 22.32 in  
Diameter: 22.20 in  
Weight: 9.1 kg

## Design

Material impression: Aluminum  
Color of housing: Silver gray

## Electric

System power: 85 W  
Voltage: 230-240 V AC  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Designation labels: CE