




Product data sheet

SINTESI SYSTEM - SUSPENSION - DARK OPTICS - UGR<LT/>19 3000K CRI 80 56W CLD-D-D WHITE
22010014-3941
DISANO



Housing: in extruded 6060 aluminium alloy. Removable extruded aluminium 6060 alloy top cover to allow electrical line connection. Injection-moulded ABS V0 end caps. Optics: dark light double parabolic louvers in high gloss 99.99 aluminium, anti-dazzle and anti-iridescent, very low luminance, and PDV treatment. : UGR<lt/>19, according to standard EN 12464. Coating: epoxy polyester powder coating resistant to UV rays. LED: 80%: 50000h (L80B20) Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471.: EN60598-1. With degree of protection according to EN60529. Warnings: suspensions not included, to be purchased separately.

Light output 1



1 x LED			
Nominal lamp power	56 W	LOR	100%
Lamp flux	4670 lm	Total flux	4670 lm
Luminous efficacy	83 lm/W	Total power	56 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 91.02 in
Width: 2.76 in
Height: 3.50 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 56 W
Appliance Class: I

Protection

IP: 40
IK: 07
Designation labels: CE