Product data sheet


ANDHO MIDI MAST
722271.004.1.76
RZB



IP 65 IK 08

Series: ANDHO midi Surface-mounted LED projector in a timeless design. Housing: die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Integral membrane valve for pressure compensation and avoidance of condensation. MIRO-SILVER reflectors for outstanding efficiency or polycarbonate lenses for the best uniformity of the light cone. Cover clear single-pane toughened glass, edge printed. COB LED with socket for easy replacement. Projector: horizontal rotation range: 40°, vertical swivel range: 90°. Lockable projector orientation. Driver integrated. Colour: silver, matt (approx. RAL 9006) Length: 261 mm Width: 154 mm Height: 216 mm Lamp: LED System power: 39 W Rated luminous flux: 5150 lm Luminous efficiency: 132 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39 W	CRI	80
Total flux	5150 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	50%
		Total power	39 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 6.06 in
Width: 10.28 in
Height: 8.50 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 39 W

Protection

IP: 65
IK: 08