


# Product data sheet


PERCEIVE  
24PD-95-PB1-L830  
COOPER LIGHTING



IP  
47

Uses patent pending Perceive™ Technology based on cognitive science, Unique optical patterns add dimensionality and visual interest, Low-glare solutions available – UGR less than 16, Durable extruded aluminum regressed door provides service from below, Efficacy up to 137 lumens per watt, 80CRI and 90CRI options in 3000K, 3500K, 4000K, 5000K CCT, Available in 2x2, 2x4, and 1x4 sizes, Bottom surface can be wiped down for easy cleaning and maintenance, Flexible – recessed, drywall, and surface mount, Integrated control available - WaveLinx, WaveLinx Lite, DLVP

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 73 W     | CRI         | 80     |
| Total flux         | 9107 lm  | LOR         | 100%   |
| Luminous efficacy  | 125 lm/W | Total power | 73 W   |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 24.00 in  
Width: 48.00 in  
Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 73 W

## Protection

IP: 47