


# Product data sheet

ARTERA LED ED 49W 7350LM 4000K IP66 O7 - FOR AREA LIGHTING GRAPHITE II  
130355.5L042.070  
LUG



Modern urban-park luminaire for LED light sources with multiple mounting options and distinctive design. In order to mount the luminaire, a suitable mounting bracket (accessories) must be ordered. High efficacy to 150 lm/W Mounting on pillar, on outriggers, with mounting brackets (on request). Body high pressure die-cast aluminum. Lateral Surface Wind Exposed 0.048 m². Power supply efficiency 90% Power 220-240V 50/60Hz Lifetime LED (L90) 100 000 h Available on request: LLOC, twilight sensor, 10kV surge protection, NTC, NEMA connector, ZHAGA connector, iBLOC controller Additional information: luminaires are not equipped with a tight connector. Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application:avenues, sidewalks, parks, residential, public spaces, Railway stations, facades, promenade, roads, local roads, town roads, residential area roads, parking areas, playgrounds. Type of optics: O7 - for area lighting

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	49 W	CRI	70
Total flux	7350 lm	LOR	100%
Luminous efficacy	150 lm/W	Total power	49 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.65 in  
Width: 21.65 in  
Height: 3.94 in

## Adjustability

Fixed

## Design

Color of housing: Anthracite / graphite

## Electric

System power: 49 W  
Appliance Class: II

## Protection

IP: 66  
IK: 08