



# Product data sheet

MAXI ROOF DRIFT  
7040-0-5-987-XX  
UNILAMP



Description Square in shape DRIFT wall and ceiling lights have a robust aluminium construction and impact resistant polycarbonate diffuser cover. DRIFT with LED unit is also available with built-in microwave sensor and hi-low light function. The high protection rating of IP65 and IK09 allows DRIFT to be installed in the harshest outdoor environments. With the diffused light distribution, it provides good low glare general lighting to private and public areas. The front cover is available in various designs; moreover, DRIFT is available in 2 sizes with the choice of 5 different colors. • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. Replaceable for future upgrade. • Optional with motion detector (Microwave Sensor). • Quick connector for easy installation. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x LED			
Nominal lamp power	21 W	LOR	65%
Lamp flux	2230 lm	ULOR	5%
Luminous efficacy	106 lm/W	Total flux	1440 lm
CCT	3000 K	Total power	23 W
CRI	80		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 14.00 in

Width: 7.68 in

Height: 14.00 in

## Adjustability

Fixed

## Electric

System power: 23 W

Controller: DALI

Appliance Class: I

## Protection

IP: 65

IK: 10