Product data sheet

RADO 7 RECESSED WALL LUMINAIRES RA-40711-W40

LIGMAN








- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Two cable entries for through wiring - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Toughened glass diffuser - Integral control gear

Light output 1 (integrated)



| Lamp type | LED | CCT | 4032 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 20.3 W | CRI | 80 |
| Total flux | 1399 lm | LOR | 100% |
| Luminous efficacy | 69 lm/W | Total power | 20.3 W |

Mounting mode

Wall mounted

Shape and measurements

Length: 9.65 in Width: 9.65 in Height: 4.53 in Weight: 6.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 20.3 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65 IK: 09

Surface temperature: 40°C