


# Product data sheet

VOLKMAR I (1-ARMED)  
9.870.0203.08  
LEIPZIGER LEUCHTEN




For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	73%
Lamp flux	2000 lm	ULOR	28%
Luminous efficacy	25 lm/W	Total flux	1454 lm
CCT	3400 K	Total power	59 W
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	73%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	33 lm/W	Total flux	2908 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Pole top mounted, Ceiling mounted

## Shape and measurements

Height: 28.35 in  
Diameter: 16.14 in

## Design

Material impression: Matt

## Electric

System power: 59-89 W  
Ballast: ECG

## Protection

IP: 55  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: 32...95°F