

# Product data sheet

FLAT POLYMER0  
311974.002.4  
RZB




IP  
40

IK  
10

Series: FLAT POLYMER0 Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205&#160;mm, h 35&#160;mm. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. Colour: white Diameter: 360&#160;mm Height: 100&#160;mm Suspension length: 200-1300&#160;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 19&#160;W Rated luminous flux: 1900&#160;lm Luminous efficiency: 100&#160;lm/W Control gear: AC Strom, dim.Ph.an-/abschnitt Protection class: I Type of protection: IP&#160;40

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 19 W     | CRI         | 80     |
| Total flux         | 1900 lm  | LOR         | 100%   |
| Luminous efficacy  | 100 lm/W | ULOR        | 11%    |
|                    |          | Total power | 19 W   |

## Mounting mode

Pendant

## Electric

System power: 19 W

## Shape and measurements

Height: 3.94 in  
Diameter: 14.17 in

## Protection

IP: 40  
IK: 10

## Adjustability

Fixed