
Product data sheet

TECHNO TRACK 2.0 - 3M - POWER SWITCH - SYMMETRIC 30°X30° 4000K CRI 80 35W CLD-D-D BLACK
22301531-1241


DISANO



IP 40 IK 03

Housing: extruded aluminium, with universal adapter for electrified cable track and integrated driver as standard with switch for total power selection. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: RG1 : EN60598-1. With degree of protection according to EN60529. Equipment: Version with universal adapter to be used with Omnitrack power track, DALI dimmable version to be used with Omnitrack PLUS (power track to be purchased separately). POWER SWITCH: standard, the luminaire has a driver with a switch for selecting the total power output (4 power selections). Within a single unit, you have a luminaire that can meet any design specification. 600 mm version = 18W-20W-22W-24W 1493 mm version = 35W-40W-45W-50W Mounting: The fixture can be easily and, above all, safely hooked to the track with the clips thanks to the mechanical safety locking system. The fastening adapter is also used to make electrical connections and install Techno Track 2.0 on electrified track systems. As standard, the luminaire has a driver with a switch for selecting the total power output (4 power selections). Within a single unit, you have a luminaire that can meet any design specification. Easy installation: The special technology used to develop the adapter ensures the perfect alignment of the modules thanks to the absence of any lateral protrusions. This allows acting on individual modules in order to guarantee a final “continuous light” effect. Another notable feature is the mechanical joint integrated into the luminaire’s body, enabling individual modules to tilt independently up to 30°. This feature grants users the ability to focus the light beam on the intended area.

Light output 1



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	5075 lm	Total flux	5075 lm
Luminous efficacy	145 lm/W	Total power	35 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 58.78 in
Width: 4.72 in
Height: 1.18 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 35 W
Appliance Class: I

Protection

IP: 40
IK: 03
Designation labels: CE