

Product data sheet

VOLKMAR I (3-ARMED)
9.870.0185.08
LEIPZIGER LEUCHTEN



IP
55


For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1




| | | | |
|------------------------------|---------|-------------|---------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 26 W | LOR | 73% |
| Lamp flux | 1800 lm | ULOR | 28% |
| Luminous efficacy | 47 lm/W | Total flux | 1309 lm |
| CCT | 2899 K | Total power | 28 W |
| CRI | 90 | | |

Light output 2



| | | | |
|------------------------------|---------|-------------|---------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 26 W | LOR | 73% |
| Lamp flux | 1800 lm | ULOR | 28% |
| Luminous efficacy | 47 lm/W | Total flux | 1309 lm |
| CCT | 2899 K | Total power | 28 W |
| CRI | 90 | | |

Light output 3



1 x Compact fluorescent lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 26 W | LOR | 73% |
| Lamp flux | 1800 lm | ULOR | 28% |
| Luminous efficacy | 47 lm/W | Total flux | 1309 lm |
| CCT | 2899 K | Total power | 28 W |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in

Diameter: 16.14 in

Electric

System power: 84 W

Protection

IP: 55