Product data sheet

ASY WINK 115 LED GE 2700K MEDIUM WHITE STRUC 13071309

MODULAR






1 v I ED




The new Modular recessed spot Not only Wink's technical ingenuity may best be called remarkable, but also its sense of humor. As its name recalls, Wink is a recessed spotlight that likes to wink at you. The straightforward approach, in combination with refined lines and detailed workmanship, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. Wink is perfect for any residential or hospitality project, thanks to its symmetric or asymmetric lighting experience. Its identical design allows you to combine both versions, in order to create different lighting effects in the same room.

Light output 1




I X LED	
Nominal lamp power	11 W
Lamp flux	1002 lm
Luminous efficacy	64 lm/W
CCT	2700 K
CRI	90

LOR	90%
Total flux	902 lm
Total power	14.2 W



I X LED	
Nominal lamp power	23.4 W
Lamp flux	1657 lm
Luminous efficacy	56 lm/W
CCT	2700 k
CRI	90

LOR	90%
Total flux	1492 lm
Total power	26.7 W



1 x LED			
Nominal lamp power	16.2 W	LOR	90%
Lamp flux	1321 lm	Total flux	1189 lm
Luminous efficacy	61 lm/W	Total power	19.5 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.53 in Width: 4.53 in Height: 3.94 in Weight: 0.87 kg

Adjustability

Fixed

Electric

System power: 14.2-26.7 W

Appliance Class: III

Protection

IP: 54