Product data sheet

ENØK/ECON DIGITAL WHITE 8+2W LED 3000K RA>80 5046181184

SG ARMATUREN





L








Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated quick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light. Light distribution: Direct Light technic LED (exchangeable) 8+2W 3000K Ra>80 SDCM 3 L70/B50 >45.000 hrs Ta=25°C Control/Dimming Wireless Actuator Protection Class II IP44 IK10 Fire protection class: 850°C - 30s Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor Screwless terminal block

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	740 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	6%
		Total power	10 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.81 in Width: 11.81 in Height: 3.74 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W Appliance Class: II

Protection

IP: 44 IK: 10