


# Product data sheet

NADJA V (WITH SHIELD ON SIDE FACING BUILDING, CLEAR ATTACHMENT)  
9.870.2072.95  
LEIPZIGER LEUCHTEN



Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	150 W	LOR	86%
Lamp flux	17000 lm	Total flux	14656 lm
Luminous efficacy	83 lm/W	Total power	176 W
CCT	2000 K		
CRI	25		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 20.08 in  
Diameter: 20.08 in

## Design

Material impression: Matt  
Color of housing: Black

## Electric

System power: 176 W  
Ballast: ECG

## Protection

IP: 55  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...95°F