

# Product data sheet

P-INF R100L LED750-930 LDO SM TL


60817795

ZUMTOBEL



LED ceiling-recessed luminaire without trim, "Stable White"; shielding angle 60°; lamp(s): LED750-930; Colour rendering Ra > 90, colour temperature 3000 K (warm white); Chromaticity tolerance (initial MacAdam): 2; total power: 9 W; Luminaire luminous flux: 882 lm, Luminaire efficacy: 98 lm/W; service life: 50000h at 95% luminous flux; includes control unit Slave luminaire for DALI control (DALI only); modular, high quality optical unit consisting of reflector and LED light chamber integrated in optimised thermal management of die-cast aluminium; smooth reflector matt aluminized finish; reflector made of high-quality, UV-resistant polycarbonate; luminaire unit fitted quickly without tools using twist-and-lock mechanism; IP44\_IP20; luminaire wired with halogen-free leads; power connection: 5-pole connector terminal, loop-in/loop-out possible; mains voltage: 220-240V / 0/50/60Hz, for use with 220V DC central battery; tool-free quick installation using antislip spring clips in ceilings of thickness 1-40mm; ceiling cutout: 100mm, recess depth: 100mm (for ceiling thicknesses 1-15mm); weight: 0.52 kg Note: UGR<19 for office applications compliant with EN12464 (depending on luminaire type) Note: Please order seating ring (planar ring) separately for installing the luminaire flush with the ceiling (see Accessories)

## Light output 1



### 1 x LED

Nominal lamp power	9 W	LOR	100%
Lamp flux	1100 lm	Total flux	1101 lm
Luminous efficacy	122 lm/W	Total power	9 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 3.62 in

Diameter: 4.29 in

Weight: 0.5 kg

## Design

Material impression: Aluminum

Color of housing: White

## Electric

System power: 9 W

Controller: DALI

Appliance Class: II

## Protection

IP: 20

Designation labels: CE, ENEC