Product data sheet


SAFESITE LED HIGH BAY 19500 LUMENS, WIDE DISTRIBUTION, GLASS LENS
HED7WC2CXXXXXN
DIALIGHT



IP 66 IK 05

SafeSite LED High Bay 19,500 Lumens 129 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Glass Lens Class I Div 2 Groups A,B,C,D Class II Div 1 Groups E,F,G Class II Div 2 Groups F,G Class III Div 1&2 UL 844 (wet locations) CSA C22.2 No. 137-M81 NEMA 4X IK05 Wide Distribution IP66/67 LM79 Tested IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	128.4 W	CRI	80
Total flux	19817 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	128.4 W

Mounting mode

Pendant

Shape and measurements

Length: 15.94 in
Width: 15.94 in
Height: 5.04 in

Adjustability

Rotatable, Tiltable

Electric

System power: 128.4 W
Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC
Appliance Class: I

Protection

IP: 66
IK: 05

Other operating numbers

Ambient temperature range: -40...149°F