

Product data sheet

LINE50HEX
LH50A-298401-LXXXM
EGLO




surface mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	16.75 W	CRI	80
Total flux	1982 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	16.75 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	16.75 W	CRI	80
Total flux	1982 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	16.75 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	16.75 W	CRI	80
Total flux	1982 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	16.75 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	16.75 W	CRI	80
Total flux	1982 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	16.75 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	16.75 W	CRI	80
Total flux	1982 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	16.75 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	16.75 W	CRI	80
Total flux	1982 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	16.75 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 117.64 in

Width: 101.89 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 100.5 W

Protection

IP: 20

Designation labels: CE