Product data sheet

RUNDO24 290-260I-10GIM3/830, S
290-260I-10GIM3/830
HALLA



IP 40

290-260I-10GIM3/830, S Luminaire surface/wall mounted/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 630 x 630 x 24 mm Type of installation: Surface, Wall mounted, Suspended Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	250 lm	LOR	100%
Luminous efficacy	167 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	39.4 W	CRI	80
Total flux	5570 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	39.4 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 0.94 in
Diameter: 24.80 in

Adjustability

Fixed

Electric

System power: 40.9 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 40