Product data sheet

CLARA VII (WITH SHIELD ON SIDE FACING BUILDING, CLEAR ATTACHMENT) 9.767.2032.25


LEIPZIGER LEUCHTEN





For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination -Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately

Light output 1



1 x High pressure sodium vapo	our lamp
Nominal lamp nower	70 W

Lamp flux	5600 lm
Luminous efficacy	34 lm/W
CCT	2000 K
CRI	25

LOR 50%
ULOR 8%
Total flux 2825 lm
Total power 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 27.56 in Diameter: 29.92 in Electric

System power: 83 W