


Product data sheet

RINQ SD 1500 WAND-DECKEN AUFBAULEUCHTE 66W 3000K SILBER PMMA OPAL
445-9115019180V1
MOLTO LUCE




RINQ WAND-DECKEN AUFBAULEUCHTE aus Aluminium, silber, ähnlich RAL 9006,satinierter PMMA Opaldiffuser Lichtaustritt direkt, mit Betriebsgerät, IP20

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8 W	CRI	80
Total flux	688 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.05 in

Width: 59.06 in

Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 64 W

Appliance Class: I

Protection

IP: 20

IK: 02