
Product data sheet


LESS IS MORE VARIO P
312704.004.1
RZB



IP 20 IK 03

Series: LESS IS MORE vario Linear pendant luminaire for aesthetically sophisticated lighting. Housing made of extruded aluminium profile, powder-coated. End cap aluminium powder-coated, without visible screws. Canopy made of aluminium, powder-coated. Diffuser made of non-yellowing plastic (PMMA) microprismatic. Specially matched 2-component optical system for glare-free light at the workstation (suitable for use in environments with computer screens in accordance with EN 12464-1). Direct/indirect light emission. Suitable for pendant. 2-point steel cable suspension freely positionable and infinitely height-adjustable. Special lengths available on request. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. Colour: silver, matt (approx. RAL 9006) Length: 1971 mm Width: 110 mm Height: 88 mm Suspension length: 2000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 Light source: LED Socket lamp2: Without base Colour temperature: 4000K System power: 49 W Rated luminous flux: 7150 lm Beam angle Down: 82° / 82° Luminous efficiency: 146 lm/W Control gear: Regulated power supply Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	49 W	CRI	80
Total flux	7150 lm	LOR	100%
Luminous efficacy	146 lm/W	ULOR	13%
		Total power	49 W

Mounting mode

Pendant

Shape and measurements

Length: 4.33 in
Width: 77.60 in
Height: 3.46 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 49 W

Protection

IP: 20
IK: 03