



Product data sheet

PEGASUS_4W_IP65_NEUTRAL_WIDE
84701303_
PETRIDIS



A floodlight with LED technology and high protection degree (IP65). It is ideal for outdoor lighting and for impressive highlighting of facades. Technical Features - Body from die-cast aluminium, painted electrostatically in selected colour. - Tempered protection glass 3mm. - Pure light without IR/UV radiation. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Supplied with 3x0,75mm PVC 1,5m cable with anti-siphon (for 230V version) and with 2x0,75mm PVC 1,5m cable with anti-siphon (for 24V version). Upon request: Available with highest colour rendering index (CRI)

Light output 1



1 x LED			
Nominal lamp power	4 W	LOR	83%
Lamp flux	466 lm	Total flux	387 lm
Luminous efficacy	116 lm/W	Total power	4 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard, Ceiling mounted, Floor mounted, Wall mounted

Shape and measurements

Height: 1.85 in
Diameter: 2.72 in

Adjustability

Rotatable, Tilttable

Design

Material impression: Aluminum, Chrome, Glass

Electric

System power: 4 W
Appliance Class: I

Protection

IP: 65
IK: 06
Resistant to impact of balls
Designation labels: CE