Product data sheet


LUCAS III (1-ARMED) 9.853.3142.15 LEIPZIGER LEUCHTEN






Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury vapour lamp | 1 x High | pressure | mercury | vapour | lamp |
|---------------------------------------|----------|----------|---------|--------|------|
|---------------------------------------|----------|----------|---------|--------|------|

| Nominal lamp power | 50 W | LOR | 84% |
|--------------------|---------|-------------|---------|
| Lamp flux | 2000 lm | Total flux | 1675 lm |
| Luminous efficacy | 28 lm/W | Total power | 59 W |
| CCT | 3400 K | | |
| CRI | 54 | | |



| 1 x High pressure mercury vapour lamp | | | |
|---------------------------------------|------|-----|--|
| Nominal lamp power | 80 W | LOR | |

| Nominal lamp power | 80 W | LOR | 84% |
|--------------------|---------|-------------|---------|
| Lamp flux | 4000 lm | Total flux | 3351 lm |
| Luminous efficacy | 38 lm/W | Total power | 89 W |
| CCT | 3400 K | | |
| CRI | 54 | | |

| Mounting mode | Electric |
|------------------------|-----------------------|
| Pole top mounted | System power: 59-89 W |
| Shape and measurements | Protection |
| Height: 19.69 in | IP: 55 |
| Diameter: 22.44 in | |