Product data sheet

LISET 2.0 HE - DIRECT LIGHT SUSPENSION - 90° 4000K CRI 80 56W CLD BLACK
22303039-00
DISANO



IP 40 IK 07

Housing: in extruded aluminium with die-cast aluminium end caps. Diffuser: in polycarbonate Coating: epoxy polyester powder coating resistant to UV rays. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Warnings: suspensions not included, to be purchased separately. On request: - CRI<It/>90. - PUSH-DIMM version, subcode -1245 (4000K) or -3945 (3000K). - 1h EM version, subcode -09 (4000K) ot -0928 (3000K). - 3h EM version, subcode -31 (4000K) or -3957 (3000K). - wiring through continous row, subcode -0072.

Light output 1



1 x LED

Nominal lamp power	56 W	LOR	100%
Lamp flux	6673 lm	Total flux	6672 lm
Luminous efficacy	119 lm/W	Total power	56 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 89.57 in
Width: 1.97 in
Height: 2.36 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 56 W
Appliance Class: I

Protection

IP: 40
IK: 07
Designation labels: CE