
Product data sheet

CLARA III (CLEAR ATTACHMENT) 9.763.2032.05



For medium/high light requirements, mounting height 4.00 - 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized -High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

IP 55

r x ngn procedio occidini reporti lamp			
Nominal lamp power	70 W	LOR	51%
Lamp flux	5600 lm	ULOR	9%
Luminous efficacy	35 lm/W	Total flux	2883 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Pole top mounted Shape and measurements Height: 23.62 in Diameter: 29.92 in

Electric

System power: 83 W

Protection

IP: 55