

# Product data sheet

FLAT POLYMERO KREIS  
311925.002.1  
RZB




IP  
40

IK  
03

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (PMMA). Diffuser fastening: push lock. Available Colours: white Type of Installation: Pendant Dimensions: D 360, H 87 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1350lm System power: 27W Beam Angle: 128° Unified Glare Ratio: 19,0 EEC: A+

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 27 W    | CRI         | 80     |
| Total flux         | 1350 lm | LOR         | 100%   |
| Luminous efficacy  | 50 lm/W | ULOR        | 19%    |
|                    |         | Total power | 27 W   |

## Mounting mode

Pendant

## Shape and measurements

Height: 3.43 in  
Diameter: 14.17 in

## Adjustability

Fixed

## Electric

System power: 27 W

## Protection

IP: 40  
IK: 03