Product data sheet

URBINO LED 102W 14500LM 4000K IP66 O33 - FOR EXPRESS ROADS GRAY I
130222.5L781.121


LUG



IP 66 IK 09

Professional streetlight luminaire for LED light sources. High efficacy to 156 lm/W Mounting: on pillar ø60/48mm, on pillar ø76mm - modification .829, on outriggers ø60/48mm, on outriggers ø76mm - modification .829. Body: high pressure die-cast aluminum. Lateral Surface Wind Exposed: 0.039 m². Power supply efficiency>95% Power: 220-240V 50/60Hz. Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, knife switch, 10kV surge protection, NTC. Additional information: Tilt adjustment: -15° to +15° (every 5°). Additional equipment: additional anti-corrosive protection (index extension: .985), access to the driver chamber without the use of tools (index extension: .825), luminaire with holder for mounting on a ø76mm pillar (index extension: .829). Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenades, cycle paths. Type of optics: O33 - for express roads

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	102 W	CRI	70
Total flux	14500 lm	LOR	100%
Luminous efficacy	142 lm/W	Total power	102 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.65 in
Width: 9.84 in
Height: 3.94 in

Adjustability

Tiltable

Design

Color of housing: Silver gray

Electric

System power: 102 W
Appliance Class: I

Protection

IP: 66
IK: 09